



Payal Polyplast Pvt. Ltd.

E-24 Netaji Subhash Marg, Darya Ganj, Delhi - 110002
Telefax: 91-1-23250063; E-mail: sales@payalgroup.com



ISO 9001:2001 & ISO 14001:2004
Certified Company

SECTION I. MATERIAL IDENTIFICATION & USE

MATERIAL NAME	Di-n-BUTYL PHTHALATE	
MANUFACTURER'S NAME & ADDRESS	PAYAL POLYMERS PVT LTD PLOT NO-87,88,102 & 103, PANCHAL UDYOG NAGAR BHIMPORE, DAMAN- 396210	
SUPPLIER'S NAME & ADDRESS	PAYAL POLYMERS PVT LTD PLOT NO-87,88,102 & 103, PANCHAL UDYOG NAGAR BHIMPORE, DAMAN- 396210	
CHEMICAL NAME:	DI-n-BUTYL PHTHALATE	CHEMICAL IDENTITY- $C_6H_4-1,2-(COOC_4H_9)_2$
TRADE NAME:	n-DBP	MOLECULAR WEIGHT-278
& SYNONYMS:	DI -n-BUTYL PHTHALATE	PRODUCT USE PLASTICIZER FOR RESINS & ELASTOMERS

SECTION II. HAZARDOUS INGREDIENTS OF MATERIAL

NAME	% CONC	CAS NO	UN NO	LD 50	LC 50
Di-n-BUTYL PHTHALATE	99-100	84-74-2	DNA	DNA	DNA

SECTION III. PHYSICAL DATA FOR MATERIAL

STATE	LIQUID	APPEARANCE	COLORLESS
ODOUR	ODOUR LESS	SPECIFIC GRAVITY	1.040
ODOUR THRESHOLD	NOT APPLICABLE	VAPOUR PRESSURE	1.32 mm Hg AT 150° C
BOILING POINT	340° C	VAPOUR DENSITY	9.6 (air=1)
MELT, FREEZING POINT	-35° C	EVAPORATIONAL RATE	NOT PERTINENT
p ^H	7	SOLUBILITY IN WATER	NEGLECTIBLE
COEFFICIENT OF WATER/OIL DISTRIBUTION	0	BULK DENSITY	NOT PERTINENT

SECTION IV. FIRE AND EXPLOSION HAZARD

FLAMMABILITY	IF PRE HEATED	SPECIAL PROCEDURE	USE FOAM
MEANS TO EXTINGUISH	FOAM	LOWER EXPLOSIVE LIMIT	DNA
FLASH POINT(by method)	NOT PERTINENT	UPPER EXPLOSIVE LIMIT	DNA
AUTO IGNITION TEMP	NOT PERTINENT	NFPA CLASSIFICATION	DNA
HAZARDIOUS COMBUSTION PRODUCT	SMOKE	TDG CLASSIFICATION	DNA
MECHANICAL IMPACT		SENSITIVITY TO STATIC DISCHARGE	NOT KNOWN
SENSITIVITY	NIL		

SECTION V. REACTIVITY DATA

CHEMICAL STABILITY	NORMALLY STABLE
INCOMPATIBLE SUBSTANCE	OXIDIZING AGENT
REACTIVITY CONDITION	AT BOILING POINT
HAZARDOUS DECOMPOSITION PRODUCT	SMOKE

SECTION VI. TOXICOLOGICAL PROBLEMS

SKIN CONTACT	IRRITATION DERMATITIS
SKIN ABSORPTION	NIL
EYE CONTACT	IRRITATION
INHALATION	UNPLEASANT
INGESTION	SLIGHTLY HAZARDOUS
IRRITANCY	SLIGHT SENSATION TO VULNERABLE SKIN
SENSITISATION TO MATERIAL	CARCINOGENIC EFFECT
SYNERGISTIC MATERIAL	SOLVENT

SECTION VII. PREVENTIVE MEASURES

PROTECTIVE EQUIPMENTS	HAND GLOVES
ENGINEERING CONTROL	CHARGING MECHANICALLY
LEAK OR SPILL PROCEDURE	ABSORB ON DRY SAND
WASTE CONTROL PROCEDURE	SAND OR EARTHEN BOUNDS
HANDLING & STORAGE	STORE IN LEAK PROOF CONTAINER AND TRANSFER THROUGH PIPELINE
SPECIAL SHIPPING INFORMATION	FLOATS ON WATER & VISCOSITY AT ROOM TEMPT 0.203 POISE AT 20° C

SECTION VIII. FIRST AID MEASURE

REMOVE CONTAMINATED CLOTHING, WIPE OFF AFFECTED SKIN AND WASH WITH SOAP AND WATER.